

REMARKS

§132.

Early action on the merits is earnestly solicited.

Respectfully submitted,

NATH & ASSOCIATES PLLC

By:

Gary M. Nath
Registration No. 26,965
Customer No. 20529

Date: November 15, 2001
NATH & ASSOCIATES PLLC
1030 15th Street, NW - 6th Floor
Washington, D.C. 20005
GMN/ljs:24810:AMENDpreml

THE

MARKED UP COPY OF CLAIM AMENDMENTS:

(Amended) 3. Circuit configuration as defined in Claim 1 [or 2], characterized in that a pole of the supply voltage source (U) is connected to an input of two-wire sensor (S) via a HART® resistor (RH), the drain source path of a field effect transistor (T1), and the current-limiting resistor (R1), the other input of which sensor is connected to the other pole of the supply voltage source (U) via the second connection line (V2) that the HART® resistor (RH), the drain source path of the field effect transistor (T1) and the current-limiting resistor (R1) are positioned in the first connection line (V1), that the source electrode of the field effect transistor (T1) is connected to the second connection line (V2) via a series circuit comprising a first and second limiting diode (D1, D2), that a first resistor (R4) is positioned parallel to the second limiting diode (D2), that the joint node of the second limiting diode (D2) and the first resistor (R4) is connected to the base of a transistor (T2), the collector of which is connected to the gate

electrode of field effect transistor (T1) via a second resistor (R3), and the emitter of which is connected to the second connection line (V2), and that the gate electrode of the field effect transistor (T1) is connected to the source electrode via a third resistor (R2).

- (Amended) 5. Circuit configuration as defined in claim 4 [one of the preceding claims], characterized in that the series connected limiting diodes (D1 through D6) are oppositely poled.

0999742-11501